




UNIMECH GROUP, MALAYSIA



A MEMBER OF UNIMECH GROUP, MALAYSIA

GATE VALVE FLANGED END 150LBS (RISING STEM)

Model : ARV-801FE(A)-R



Features :

Face to face is according to ANSI B16.10

Flange drilled is according to ANSI B16.1

Working Pressure : 150 PSI

Test Pressure Shell : 24 kgf/cm²

Seat : 17.5 kgf/cm²

Working Temperature : ≤200°C

Technical Data

Material

No	PART	MATERIAL
1	BODY	CAST IRON (A126B)
2	SEAT SEAL RING	CAST BROZE / STAINLESS STEEL
3	DISC	CAST IRON (A126B)
4	BONNET	CAST IRON (A126B)
5	PACKING	GRAPHITE
6	GLAND	DUCTILE IRON (A395)
7	STEM	STAINLESS STEEL (410)
8	HANDWHEEL	CAST IRON (A126B)

Dimension in mm

SIZES	1.1/2"	2"	2.1/2"	3"	4"	5"	6"	8"	10"	12"
DN	40	50	65	80	100	125	150	200	250	300
L	165	178	190	203	230	254	267	292	330	356
H	254	267	279	305	406	457	559	711	889	1117
D	127	152	178	191	229	254	279	343	406	483
Wt. (kg)	26.5	29	34	44.5	62.5	83	110	177	279	364

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.

Our Ref. : ARG6- 11/23