



ARITA MILD STEEL BLIND FLANGE (ANSI 150)

DESCRIPTION	CLASS	SIZE	F.G	OD	PCD	ID	HOLE
			THK(TA)				
			mm				
			± 0.7	± 0.5		± 0.5	(N) X (DJ)
blind flange	150	1/2"	13.5	89.0	60.5	-	4x15mm
blind flange	150	3/4"	13.5	98.0	70.0	-	4x15mm
blind flange	150	1"	16.5	108.0	79.5	-	4x15mm
blind flange	150	1 1/4"	16.5	118.0	89.0	-	4x15mm
blind flange	150	1 1/2"	16.5	127.0	98.5	-	4x15mm
blind flange	150	2"	16.5	152.0	120.5	-	4x19mm
blind flange	150	2 1/2"	18.5	178.0	139.5	-	4x19mm
blind flange	150	3"	18.5	191.0	152.5	-	4x19mm
blind flange	150	4"	18.5	229.0	190.5	-	8x19mm
blind flange	150	5"	20.5	254.0	216.0	-	8x23mm
blind flange	150	6"	20.5	279.0	241.5	-	8x23mm
blind flange	150	8"	20.5	343.0	298.5	-	8x23mm
blind flange	150	10"	20.5	406.0	362.0	-	12x25mm
blind flange	150	12"	23.5	483.0	432.0	-	12x25mm
blind flange	150	14"	23.5	533.0	477.0	-	12x28mm
blind flange	150	16"	23.5	597.0	540.0	-	16x28mm
blind flange	150	18"	26.5	635.0	578.0	-	16x30mm
blind flange	150	20"	26.5	699.0	635.0	-	20x30mm
blind flange	150	24"	26.5	813.0	749.5	-	20x30mm

Arita Standard

Arita Flange Thickness Tolerance ± 0.7 mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.