



ARITA MILD STEEL BLIND FLANGE (JIS 10K)

DESCRIPTION	CLASS	SIZE	F.G	OD	PCD	ID	HOLE
			THK(TA)				
			mm	mm	mm	mm	(N) X (DJ)
			±0.7	±0.5		±0.5	
blind flange	10K	1/2"	13.5	95	70	-	4x15mm
blind flange	10K	3/4"	13.5	100	75	-	4x15mm
blind flange	10K	1"	13.5	125	90	-	4x19mm
blind flange	10K	1 1/4"	13.5	135	100	-	4x19mm
blind flange	10K	1 1/2"	13.5	140	105	-	4x19mm
blind flange	10K	2"	13.5	155	120	-	4x19mm
blind flange	10K	2 1/2"	13.5	175	140	-	4x19mm
blind flange	10K	3"	13.5	185	150	-	8x19mm
blind flange	10K	4"	16.5	210	175	-	8x19mm
blind flange	10K	5"	16.5	250	210	-	8x23mm
blind flange	10K	6"	16.5	280	240	-	8x23mm
blind flange	10K	8"	16.5	330	290	-	12x23mm
blind flange	10K	10"	20.5	400	355	-	12x25mm
blind flange	10K	12"	20.5	445	400	-	16x25mm
blind flange	10K	14"	23.5	490	445	-	16x25mm
blind flange	10K	16"	23.5	560	510	-	16x28mm
blind flange	10K	18"	26.5	620	565	-	20x28mm
blind flange	10K	20"	26.5	675	620	-	20x28mm
blind flange	10K	24"	26.5	795	730	-	24x30mm

Arita Standard

Arita Flange Thickness Tolerance +-0.7mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.