



**ARITA MILD STEEL BLIND FLANGE (JIS 16K / 20K)**

DESCRIPTION	CLASS	SIZE	F.G		PCD	ID	HOLE
			THK(TA)	OD			
			mm	mm			
			$\pm 0.7$	$\pm 0.5$		$\pm 0.5$	(N) X (DJ)
blind flange	16K/20K	1/2"	16.5	95	70	-	4*15mm
blind flange	16K/20K	3/4"	16.5	100	75	-	4*15mm
blind flange	16K/20K	1"	16.5	125	90	-	4*19mm
blind flange	16K/20K	1 1/4"	16.5	135	100	-	4*19mm
blind flange	16K/20K	1 1/2"	16.5	140	105	-	4*19mm
blind flange	16K/20K	2"	16.5	155	120	-	8*19mm
blind flange	16K/20K	2 1/2"	18.5	175	140	-	8*19mm
blind flange	16K/20K	3"	20.5	200	160	-	8*23mm
blind flange	16K/20K	4"	20.5	225	185	-	8*23mm
blind flange	16K/20K	5"	23.5	270	225	-	8*25mm
blind flange	16K/20K	6"	23.5	305	260	-	12*25mm
blind flange	16K/20K	8"	23.5	350	305	-	12*25mm
blind flange	16K/20K	10"	23.5	430	380	-	12*28mm
blind flange	16K/20K	12"	23.5	480	430	-	16*28mm
blind flange	16K/20K	14"	23.5	540	480	-	16*30mm
blind flange	16K/20K	16"	23.5	605	540	-	16*30mm
blind flange	16K/20K	18"	23.5	675	605	-	20*30mm
blind flange	16K/20K	20"	23.5	730	660	-	20*30mm
blind flange	16K/20K	24"	23.5	845	770	-	24*30mm

Arita Standard

Arita Flange Thickness Tolerance  $\pm 0.7$ mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.