



ARITA MILD STEEL BLIND FLANGE (JIS 5K)

DESCRIPTION	CLASS	SIZE	F.G	OD	PCD	ID	HOLE
			THK(TA)				
			mm	mm	mm	mm	(N) X (DJ)
			±0.7	±0.5		±0.5	
blind flange	5K	1/2"	13.5	80	60	-	4x12mm
blind flange	5K	3/4"	13.5	85	65	-	4x12mm
blind flange	5K	1"	13.5	95	75	-	4x12mm
blind flange	5K	1 1/4"	13.5	115	90	-	4x15mm
blind flange	5K	1 1/2"	13.5	120	95	-	4x15mm
blind flange	5K	2"	13.5	130	105	-	4x15mm
blind flange	5K	2 1/2"	13.5	155	130	-	4x15mm
blind flange	5K	3"	13.5	180	145	-	4x19mm
blind flange	5K	4"	13.5	200	165	-	8x19mm
blind flange	5K	5"	13.5	235	200	-	8x19mm
blind flange	5K	6"	13.5	265	230	-	8x19mm
blind flange	5K	8"	16.5	320	280	-	8x23mm
blind flange	5K	10"	18.5	385	345	-	12x23mm
blind flange	5K	12"	20.5	430	390	-	12x23mm
blind flange	5K	14"	23.5	480	435	-	12x25mm
blind flange	5K	16"	23.5	540	495	-	16x25mm
blind flange	5K	18"	26.5	605	555	-	16x25mm
blind flange	5K	20"	26.5	655	605	-	20x25mm
blind flange	5K	24"	26.5	770	715	-	20x28mm

Arita Standard

Arita Flange Thickness Tolerance +-0.7mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.