



ARITA MILD STEEL BLIND FLANGE (PN 10)

DESCRIPTION	CLASS	SIZE	F.G		PCD	ID	HOLE
			THK(TA)	OD			
			mm	mm			
			± 0.7	± 0.5		± 0.5	(N) X (DJ)
blind flange	PN10	1/2"	13.5	95	65	-	4x15mm
blind flange	PN10	3/4"	13.5	105	75	-	4x15mm
blind flange	PN10	1"	13.5	115	85	-	4x15mm
blind flange	PN10	1 1/4"	13.5	140	100	-	4x15mm
blind flange	PN10	1 1/2"	13.5	150	110	-	4x15mm
blind flange	PN10	2"	13.5	165	125	-	4x15mm
blind flange	PN10	2 1/2"	16.5	185	145	-	4x19mm
blind flange	PN10	3"	16.5	200	160	-	8x19mm
blind flange	PN10	4"	16.5	220	180	-	8x19mm
blind flange	PN10	5"	18.5	250	210	-	8x19mm
blind flange	PN10	6"	18.5	285	240	-	8x23mm
blind flange	PN10	8"	18.5	340	295	-	8x23mm
blind flange	PN10	10"	18.5	395	350	-	12x23mm
blind flange	PN10	12"	20.5	445	400	-	12x23mm
blind flange	PN10	14"	23.5	505	460	-	16x23mm
blind flange	PN10	16"	23.5	565	515	-	16x25mm
blind flange	PN10	18"	26.5	615	565	-	20x25mm
blind flange	PN10	20"	26.5	670	620	-	20x25mm
blind flange	PN10	24"	26.5	780	725	-	20x28mm

Arita Standard

Arita Flange Thickness Tolerance ± 0.7 mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.