



**ARITA MILD STEEL BLIND FLANGE (PN 16)**

| DESCRIPTION  | CLASS | SIZE   | F.G     | OD   | PCD | ID   | HOLE       |
|--------------|-------|--------|---------|------|-----|------|------------|
|              |       |        | THK(TA) |      |     |      |            |
|              |       |        | mm      | mm   | mm  | mm   | (N) X (DJ) |
|              |       |        | ±0.7    | ±0.5 |     | ±0.5 |            |
| blind flange | PN16  | 1/2"   | 13.5    | 95   | 65  | -    | 4x15mm     |
| blind flange | PN16  | 3/4"   | 13.5    | 105  | 75  | -    | 4x15mm     |
| blind flange | PN16  | 1"     | 13.5    | 115  | 85  | -    | 4x15mm     |
| blind flange | PN16  | 1 1/4" | 13.5    | 140  | 100 | -    | 4x19mm     |
| blind flange | PN16  | 1 1/2" | 13.5    | 150  | 110 | -    | 4x19mm     |
| blind flange | PN16  | 2"     | 13.5    | 165  | 125 | -    | 4x19mm     |
| blind flange | PN16  | 2 1/2" | 16.5    | 185  | 145 | -    | 4x19mm     |
| blind flange | PN16  | 3"     | 16.5    | 200  | 160 | -    | 8x19mm     |
| blind flange | PN16  | 4"     | 16.5    | 220  | 180 | -    | 8x19mm     |
| blind flange | PN16  | 5"     | 18.5    | 250  | 210 | -    | 8x19mm     |
| blind flange | PN16  | 6"     | 20.5    | 285  | 240 | -    | 8x23mm     |
| blind flange | PN16  | 8"     | 20.5    | 340  | 295 | -    | 12x23mm    |
| blind flange | PN16  | 10"    | 20.5    | 405  | 355 | -    | 12x25mm    |
| blind flange | PN16  | 12"    | 23.5    | 460  | 410 | -    | 12x25mm    |
| blind flange | PN16  | 14"    | 23.5    | 520  | 470 | -    | 16x25mm    |
| blind flange | PN16  | 16"    | 23.5    | 580  | 525 | -    | 16x30mm    |
| blind flange | PN16  | 18"    | 26.5    | 640  | 585 | -    | 20x30mm    |
| blind flange | PN16  | 20"    | 26.5    | 715  | 650 | -    | 20x30mm    |
| blind flange | PN16  | 24"    | 26.5    | 840  | 770 | -    | 20x30mm    |

Arita Standard

Arita Flange Thickness Tolerance +-0.7mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.