



**ARITA MILD STEEL BLIND FLANGE (PN 40)**

DESCRIPTION	CLASS	SIZE	F.G	OD	PCD	ID	HOLE
			THK(TA)				
			mm				
			$\pm 0.7$	$\pm 0.5$		$\pm 0.5$	(N) X (DJ)
blind flange	PN40	1/2"	13.5	95	65	-	4x15mm
blind flange	PN40	3/4"	13.5	105	75	-	4x15mm
blind flange	PN40	1"	16.5	115	85	-	4x15mm
blind flange	PN40	1 1/4"	16.5	140	100	-	4x19mm
blind flange	PN40	1 1/2"	16.5	150	110	-	4x19mm
blind flange	PN40	2"	20.5	165	125	-	4x19mm
blind flange	PN40	2 1/2"	20.5	185	145	-	8x19mm
blind flange	PN40	3"	20.5	200	160	-	8x19mm
blind flange	PN40	4"	20.5	235	190	-	8x23mm
blind flange	PN40	5"	20.5	270	220	-	8x25mm
blind flange	PN40	6"	20.5	300	250	-	8x25mm
blind flange	PN40	8"	23.5	375	320	-	12x30mm
blind flange	PN40	10"	23.5	450	385	-	12x30mm
blind flange	PN40	12"	23.5	515	450	-	16x30mm
blind flange	PN40	14"	23.5	580	510	-	16x30mm
blind flange	PN40	16"	23.5	660	585	-	16x30mm
blind flange	PN40	18"	26.5	685	610	-	20x30mm
blind flange	PN40	20"	26.5	755	670	-	20x30mm
blind flange	PN40	24"	26.5	890	795	-	20x30mm

Arita Standard

Arita Flange Thickness Tolerance  $\pm 0.7$ mm

The Contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify products design without prior notice.