



ARITA MILD STEEL FLAT FLANGE (ANSI 150)

DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	150	1/2"	13.5	89.0	60.5	22	4x15mm
FLANGES	150	3/4"	13.5	98.0	70.0	28	4x15mm
FLANGES	150	1"	16.5	108.0	79.5	35	4x15mm
FLANGES	150	1 1/4"	16.5	118.0	89.0	44	4x15mm
FLANGES	150	1 1/2"	16.5	127.0	98.5	49	4x15mm
FLANGES	150	2"	16.5	152.0	120.5	61	4x19mm
FLANGES	150	2 1/2"	18.5	178.0	139.5	77	4x19mm
FLANGES	150	3"	18.5	191.0	152.5	90	4x19mm
FLANGES	150	4"	18.5	229.0	190.5	116	8x19mm
FLANGES	150	5"	20.5	254.0	216.0	143	8x23mm
FLANGES	150	6"	20.5	279.0	241.5	171	8x23mm
FLANGES	150	8"	20.5	343.0	298.5	222	8x23mm
FLANGES	150	10"	20.5	406.0	362.0	276	12x25mm
FLANGES	150	12"	23.5	483.0	432.0	327	12x25mm
FLANGES	150	14"	23.5	533.0	477.0	361	12x28mm
FLANGES	150	16"	23.5	597.0	540.0	412	16x28mm
FLANGES	150	18"	26.5	635.0	578.0	463	16x30mm
FLANGES	150	20"	26.5	699.0	635.0	514	20x30mm
FLANGES	150	24"	26.5	813.0	749.5	616	20x30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.