



**ARITA MILD STEEL FLAT FLANGE (ANSI 300)**

DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	300#	1/2"	13.5	95.2	66.7	22	4*15mm
FLANGES	300#	3/4"	16.5	117.5	82.5	28	4*19mm
FLANGES	300#	1"	18.5	123.8	88.9	35	4*19mm
FLANGES	300#	1 1/4"	18.5	133.3	98.4	44	4*19mm
FLANGES	300#	1 1/2"	20.5	155.6	114.3	49	4*23mm
FLANGES	300#	2"	23.5	165.1	127	61	8*23mm
FLANGES	300#	2 1/2"	23.5	190.5	149.2	77	8*23mm
FLANGES	300#	3"	23.5	209.5	168.3	90	8*23mm
FLANGES	300#	4"	23.5	254	200	116	8*23mm
FLANGES	300#	5"	23.5	279.4	234.9	143	8*23mm
FLANGES	300#	6"	23.5	317.5	269.9	171	12*23mm
FLANGES	300#	8"	23.5	381	330.2	222	12*25mm
FLANGES	300#	10"	23.5	444.5	387.3	276	16*28mm
FLANGES	300#	12"	23.5	520.7	450.8	327	16*30mm
FLANGES	300#	14"	23.5	584.2	514.3	361	20*30mm
FLANGES	300#	16"	23.5	647.7	571.5	412	20*30mm
FLANGES	300#	18"	23.5	711.2	628.5	463	24*30mm
FLANGES	300#	20"	23.5	774.7	685.8	514	24*30mm
FLANGES	300#	24"	23.5	914.4	812.8	616	24*30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.