



ARITA MILD STEEL FLAT FLANGE (JIS 10K)							
DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	10K	1/2"	13.5	95	70	22	4x15mm
FLANGES	10K	3/4"	13.5	100	75	28	4x15mm
FLANGES	10K	1"	13.5	125	90	35	4x19mm
FLANGES	10K	1 1/4"	13.5	135	100	44	4x19mm
FLANGES	10K	1 1/2"	13.5	140	105	49	4x19mm
FLANGES	10K	2"	13.5	155	120	61	4x19mm
FLANGES	10K	2 1/2"	13.5	175	140	77	4x19mm
FLANGES	10K	3"	13.5	185	150	90	8x19mm
FLANGES	10K	4"	16.5	210	175	116	8x19mm
FLANGES	10K	5"	16.5	250	210	143	8x23mm
FLANGES	10K	6"	16.5	280	240	171	8x23mm
FLANGES	10K	8"	16.5	330	290	222	12x23mm
FLANGES	10K	10"	20.5	400	355	276	12x25mm
FLANGES	10K	12"	20.5	445	400	327	16x25mm
FLANGES	10K	14"	23.5	490	445	361	16x25mm
FLANGES	10K	16"	23.5	560	510	412	16x28mm
FLANGES	10K	18"	26.5	620	565	463	20x28mm
FLANGES	10K	20"	26.5	675	620	514	20x28mm
FLANGES	10K	24"	26.5	795	730	616	24x30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.