



ARITA MILD STEEL FLAT FLANGE (JIS 16K/20K)

DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	16K/20K	1/2"	16.5	95	70	22	4*15mm
FLANGES	16K/20K	3/4"	16.5	100	75	28	4*15mm
FLANGES	16K/20K	1"	16.5	125	90	35	4*19mm
FLANGES	16K/20K	1 1/4"	16.5	135	100	44	4*19mm
FLANGES	16K/20K	1 1/2"	16.5	140	105	49	4*19mm
FLANGES	16K/20K	2"	16.5	155	120	61	8*19mm
FLANGES	16K/20K	2 1/2"	18.5	175	140	77	8*19mm
FLANGES	16K/20K	3"	20.5	200	160	90	8*23mm
FLANGES	16K/20K	4"	20.5	225	185	116	8*23mm
FLANGES	16K/20K	5"	23.5	270	225	143	8*25mm
FLANGES	16K/20K	6"	23.5	305	260	171	12*25mm
FLANGES	16K/20K	8"	23.5	350	305	222	12*25mm
FLANGES	16K/20K	10"	23.5	430	380	276	12*28mm
FLANGES	16K/20K	12"	23.5	480	430	327	16*28mm
FLANGES	16K/20K	14"	23.5	540	480	361	16*30mm
FLANGES	16K/20K	16"	23.5	605	540	412	16*30mm
FLANGES	16K/20K	18"	23.5	675	605	463	20*30mm
FLANGES	16K/20K	20"	23.5	730	660	514	20*30mm
FLANGES	16K/20K	24"	23.5	845	770	616	24*30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.