



**ARITA MILD STEEL FLAT FLANGE (JIS 5K)**

DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	5K	1/2"	13.5	80	60	22	4x12mm
FLANGES	5K	3/4"	13.5	85	65	28	4x12mm
FLANGES	5K	1"	13.5	95	75	35	4x12mm
FLANGES	5K	1 1/4"	13.5	115	90	44	4x15mm
FLANGES	5K	1 1/2"	13.5	120	95	49	4x15mm
FLANGES	5K	2"	13.5	130	105	61	4x15mm
FLANGES	5K	2 1/2"	13.5	155	130	77	4x15mm
FLANGES	5K	3"	13.5	180	145	90	4x19mm
FLANGES	5K	4"	13.5	200	165	116	8x19mm
FLANGES	5K	5"	13.5	235	200	143	8x19mm
FLANGES	5K	6"	13.5	265	230	171	8x19mm
FLANGES	5K	8"	16.5	320	280	222	8x23mm
FLANGES	5K	10"	18.5	385	345	276	12x23mm
FLANGES	5K	12"	20.5	430	390	327	12x23mm
FLANGES	5K	14"	23.5	480	435	361	12x25mm
FLANGES	5K	16"	23.5	540	495	412	16x25mm
FLANGES	5K	18"	26.5	605	555	463	16x25mm
FLANGES	5K	20"	26.5	655	605	514	20x25mm
FLANGES	5K	24"	26.5	770	715	616	20x28mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.