



ARITA MILD STEEL FLAT FLANGE (PN 10)							
DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	PN10	1/2"	13.5	95	65	22	4x15mm
FLANGES	PN10	3/4"	13.5	105	75	28	4x15mm
FLANGES	PN10	1"	13.5	115	85	35	4x15mm
FLANGES	PN10	1 1/4"	13.5	140	100	44	4x15mm
FLANGES	PN10	1 1/2"	13.5	150	110	49	4x15mm
FLANGES	PN10	2"	13.5	165	125	61	4x15mm
FLANGES	PN10	2 1/2"	16.5	185	145	77	4x19mm
FLANGES	PN10	3"	16.5	200	160	90	8x19mm
FLANGES	PN10	4"	16.5	220	180	116	8x19mm
FLANGES	PN10	5"	18.5	250	210	143	8x19mm
FLANGES	PN10	6"	18.5	285	240	171	8x23mm
FLANGES	PN10	8"	18.5	340	295	222	8x23mm
FLANGES	PN10	10"	18.5	395	350	276	12x23mm
FLANGES	PN10	12"	20.5	445	400	327	12x23mm
FLANGES	PN10	14"	23.5	505	460	361	16x23mm
FLANGES	PN10	16"	23.5	565	515	412	16x25mm
FLANGES	PN10	18"	26.5	615	565	463	20x25mm
FLANGES	PN10	20"	26.5	670	620	514	20x25mm
FLANGES	PN10	24"	26.5	780	725	616	20x28mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.