



ARITA MILD STEEL FLAT FLANGE (PN 16)							
DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	PN16	1/2"	13.5	95	65	22	4x15mm
FLANGES	PN16	3/4"	13.5	105	75	28	4x15mm
FLANGES	PN16	1"	13.5	115	85	35	4x15mm
FLANGES	PN16	1 1/4"	13.5	140	100	44	4x19mm
FLANGES	PN16	1 1/2"	13.5	150	110	49	4x19mm
FLANGES	PN16	2"	13.5	165	125	61	4x19mm
FLANGES	PN16	2 1/2"	16.5	185	145	77	4x19mm
FLANGES	PN16	3"	16.5	200	160	90	8x19mm
FLANGES	PN16	4"	16.5	220	180	116	8x19mm
FLANGES	PN16	5"	18.5	250	210	143	8x19mm
FLANGES	PN16	6"	20.5	285	240	171	8x23mm
FLANGES	PN16	8"	20.5	340	295	222	12x23mm
FLANGES	PN16	10"	20.5	405	355	276	12x25mm
FLANGES	PN16	12"	23.5	460	410	327	12x25mm
FLANGES	PN16	14"	23.5	520	470	361	16x25mm
FLANGES	PN16	16"	23.5	580	525	412	16x30mm
FLANGES	PN16	18"	26.5	640	585	463	20x30mm
FLANGES	PN16	20"	26.5	715	650	514	20x30mm
FLANGES	PN16	24"	26.5	840	770	616	20x30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.