



ARITA MILD STEEL FLAT FLANGE (PN 40)							
DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	PN40	1/2"	13.5	95	65	22	4x15mm
FLANGES	PN40	3/4"	13.5	105	75	28	4x15mm
FLANGES	PN40	1"	16.5	115	85	35	4x15mm
FLANGES	PN40	1 1/4"	16.5	140	100	44	4x19mm
FLANGES	PN40	1 1/2"	16.5	150	110	49	4x19mm
FLANGES	PN40	2"	20.5	165	125	61	4x19mm
FLANGES	PN40	2 1/2"	20.5	185	145	77	8x19mm
FLANGES	PN40	3"	20.5	200	160	90	8x19mm
FLANGES	PN40	4"	20.5	235	190	116	8x23mm
FLANGES	PN40	5"	20.5	270	220	143	8x25mm
FLANGES	PN40	6"	20.5	300	250	171	8x25mm
FLANGES	PN40	8"	23.5	375	320	222	12x30mm
FLANGES	PN40	10"	23.5	450	385	276	12x30mm
FLANGES	PN40	12"	23.5	515	450	327	16x30mm
FLANGES	PN40	14"	23.5	580	510	361	16x30mm
FLANGES	PN40	16"	23.5	660	585	412	16x30mm
FLANGES	PN40	18"	26.5	685	610	463	20x30mm
FLANGES	PN40	20"	26.5	755	670	514	20x30mm
FLANGES	PN40	24"	26.5	890	795	616	20x30mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.