



**ARITA MILD STEEL FLAT FLANGE (TABLE E)**

DESCRIPTION	CLASS	SIZE	THK(TA) mm ±0.7	OD mm ±0.5	PCD mm	ID mm ±0.5	HOLE (N) X (DJ)
FLANGES	T/E	1/2"	13.5	95.3	66.7	22	4x15mm
FLANGES	T/E	3/4"	13.5	101.6	73.0	28	4x15mm
FLANGES	T/E	1"	13.5	114.3	82.6	35	4x15mm
FLANGES	T/E	1 1/4"	13.5	120.7	87.3	44	4x15mm
FLANGES	T/E	1 1/2"	13.5	133.4	98.4	49	4x15mm
FLANGES	T/E	2"	13.5	152.4	114.3	61	4x19mm
FLANGES	T/E	2 1/2"	13.5	165.1	127.0	77	4x19mm
FLANGES	T/E	3"	13.5	184.2	146.0	90	4x19mm
FLANGES	T/E	4"	13.5	215.9	177.8	116	8x19mm
FLANGES	T/E	5"	13.5	254.0	209.6	143	8x19mm
FLANGES	T/E	6"	13.5	279.4	235.0	171	8x23mm
FLANGES	T/E	8"	16.5	336.6	292.1	222	8x23mm
FLANGES	T/E	10"	18.5	406.4	355.6	276	12x23mm
FLANGES	T/E	12"	20.5	457.2	406.4	327	12x25mm
FLANGES	T/E	14"	23.5	527.1	469.9	361	12x25mm
FLANGES	T/E	16"	23.5	577.9	520.7	412	12x25mm
FLANGES	T/E	18"	26.5	641.4	584.2	463	16x25mm
FLANGES	T/E	20"	26.5	705.0	641.4	514	16x25mm
FLANGES	T/E	24"	26.5	825.5	755.7	616	16x25mm

Arita Standard

Arita Flange Thickness Tolerance +- 0.7mm

The contents of this literature are for informative purposes only. Arita is not responsible for suitability or compatibility of these products in relation to system requirement. For specific requirements, consult Arita or its distributors. Arita reserves the right to change or modify product design without prior notice.